



More Camera For Less. Guaranteed!

The professional and low-cost exchangeable-lens camera is suitable for indoor and outdoor use. Internal, digital video recorder with up to 16 GB of storage capacity and HiRes recording up to 3.1 megapixels. Over 30 times more detail than CIF!



HiRes Video

MOBOTIX HiRes video replaces up to 6 cameras ...

- Individual choice of lens: tele/wide-angle, day/night
- Wide range of applications from webcam to video security
- Fast, simple installation on wall, mast or ceiling
- Integrated DVR with HiRes video recording without network load
- Robust, low-maintenance and weatherproof from -30° to +60°C (-22° to +140°F), (IP65)
- Digital continuous zoom, pan and tilt
- Integrated microphone, speaker and PIR motion detector

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX AG (Australia)

• Tel: 61 2 8214 6515 • sales@mobotix.com

Australian Certified Installer/Partner:

CCTV Hire Pty Ltd

• Hire • Sales • Installation • Service

www.cctvhire.com.au

Phone: 02 9618 0444

Email: info@cctvhire.com.au

HiRes
3 Megapixel
2048 x 1536
software zoom

Skyline
Format free
each image format
freely definable

30 Frames/s
VGA (640 x 480)
12 F/s Mega

Virtual PTZ
digital pan, tilt,
zoom

Backlight
safe using CMOS
without mechanical iris

Internal DVR
internal via SD card,
external via Network

Win/Lin/Mac
Recording
via Network on PC
up to 1 Terabyte

microphone & speaker
Audio
bi-directional via IP,
variable framerates

SIP-Client with video
IP-Telephony
alarm notify,
cam remote control

Video motion
multiple windows
precision pixel-based

-22°F ... +140°F
Weatherproof
-30° ... +60°C, IP65
no heating necessary

IEEE 802.3af
PoE
network power
even in winter

Robust
no moving parts
fiber glass housing

MxCC
Licence free
Video-Management-
Software

Technical Specifications M22 Allround

Models	IT, IT-Night, Sec, Sec-Night, Sec-CSVario, Sec-R8	Virtual PTZ	Digital Pan/Tilt/Zoom, continuous 8x zoom
Lenses	22 to 135 mm format, horizontal angle 90° to 15°	Alarm/Events	Triggering of events by integrated multiple-window motion detection, external signal, temperature sensor, notification over email, FTP, IP-Telephony (VoIP, SIP), visual/acoustic alarm Pre- and post-alarm images
Sensitivity	Color: 1 lux (f=1/60 s), 0,05 lux (f=1/1 s) B/W: 0,1 Lux (f=1/60 s), 0,005 Lux (f=1/1 s)	Audio	Integrated microphone and speaker, Line-In/Line-Out, lip-synchronous audio, two-way speaker, audio recording
2 Sensors	2 x 1/2" CMOS, progressive scan	Interfaces	Ethernet 10/100, USB, Audio (microphone/speaker)
Max. image resolution	Color: 2048 x 1536 (3Mega), Black/White: 1280 x 960 (Mega)	Audio/Telephony	VoIP, SIP, two-way speaker, remote controlling of the camera in- and outputs, event notification
Image format	2048 x 1536, 1280 x 960, 1024 x 768, 800 x 600, 768 x 576 (DI), 704 x 576 (TV-PAL), 640 x 480, 384 x 288, 352 x 288, 320 x 240, 160 x 120; free image format selection (e.g. 1000 x 200 for skyline)	Security	User-/Group management, HTTPS/SSL, IP address filter, IEEE 802.1x, Intrusion Detection
Max. frame rate (M-JPEG) (Live/Recording)	VGA: 16 fps, TV-PAL: 12 fps, Mega: 6 fps, 3Mega: 4 fps	Certificates	BGV C9 ("UVV"), EMV (living environments, industry), EN 50155 (shock, vibration, temperature), CE, FCC
Max. Video stream (MxPEG) (Live/Recording/Audio)	VGA: 30 fps, TV-PAL: 24 fps, Mega: 14 fps, 3Mega: 10 fps	Power supply	Year-round Power over Ethernet (IEE 802.3af; Class 0), Netpower-Adapter, typ. 2,5 W
Image compression	MxPEG, M-JPEG, JPG, H.263 (Video-VoIP-Telephony)	Operating conditions	IP65 (DIN EN 60529), -30° to +60 °C (-22°F to +140°F)
Internal DVR	Slot for SD card (up to 16 GB)	Dimensions	WxDxL: 13,5 x 20 x 13 cm, Weight: ca. 600 g
External storage	Directly on NAS and PC/Server without additional recording software	Standard delivery	Weatherproof housing (reinforced composites - PBT-30GF), white, SecureFlex wall/ceiling mount with turn/tilt mount and concealed cabling, covers RJ45 wall outlets, incl. lens, Polycarbonate lens cover, spare lens cover, mounting parts, allen wrench, patch cable, manual, software
Software (inclusive)	Video-Management-Software MxEasy, Control room software MxControlCenter		
Image processing	Backlight compensation, automatic white balance, image distortion correction, video sensor (motion detection)		

Technical information subject to change without notice!

M22 Allround

Available Accessories M22 Allround

Standard Housing MX-M22M-Sec-D22	Pole Mount MX-MH-SecureFlex-ESWS	Glass Lens Cover MX-M22M-OPT-LCSG	Power-Adapter-Set MX-NPA-Set-DE	Power-Box 4 Cameras MX-NPR-4	ExtIO Extension Module MX-ExtIO
 <ul style="list-style-type: none"> Allround camera with individual choice of lens Incl. lens protection Fast, simple installation on wall, mast or ceiling 	 <ul style="list-style-type: none"> 3 mm stainless steel, white 2 stainless steel straps for pole diameter 60-180 mm, incl. mounting parts 	 <ul style="list-style-type: none"> Lens protection for extreme weather conditions Scratch-proof glass For all lenses 	 <ul style="list-style-type: none"> Power supply over PoE All camera models (MX30V) 	 <ul style="list-style-type: none"> Power supply for top hat rail All camera models (MX30V) 	 <ul style="list-style-type: none"> Microphone/speaker PIR sensor for motion detection, temperature sensor Integrated switch functions

L22 Super Wide Angle 90°

L32 Wide Angle 60°

L43 Wide Angle 45°

L65 Tele 31°

L135 Tele 15°

Lenses					
	approx. 90°H x 67°V at 10 m appr: 20,0 x 13,3 m	approx. 60°H x 45°V at 10 m appr: 11,5 x 8,2 m	approx. 45°H x 34°V at 10 m appr: 8,2 x 6,1 m	approx. 31°H x 23°V at 10 m appr: 5,5 x 4,0 m	approx. 15°H x 11°V at 10 m appr: 2,6 x 1,9 m

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX AG (Australia)

• Tel: 61 2 8214 6515 • sales@mobotix.com

Australian Certified Installer/Partner:

CCTV Hire Pty Ltd

• Hire • Sales • Installation • Service

www.cctvhire.com.au

Phone: 02 9618 0444

Email: info@cctvhire.com.au