

WebRelay™



WebRelay™ provides reliable remote relay control and discrete signal monitoring over any IP network.

WebRelay, can provide remote relay control in countless applications including pump and motor control, security lock systems, remote reboot, and lighting control. WebRelay's powerful and flexible design make imagination its only limit.

WebRelay also has an optically isolated input that can be used to monitor the state of devices, control the relay, or control a remote relay somewhere else on the network. This feature is useful to extend the output of a PLC to another building or to allow a switch to control a device in another state.



Features:

- No programming required
- Full control using a standard web browser or text-based XML messages
- Can operate as a Modbus/TCP slave
- Password protected
- 12 Amp relay contacts
- "On/Off" and "Pulse" modes

Optically isolated input can be used for:

- Monitoring
- Relay control
- Remote relay control (p2p)
- Auto-Reboot controller mode for remote reboot of network devices
- Selectable TCP ports
- Two-piece (8-pin) removable terminal connectors included
- DIN rail or wall-mount

Three power supply options available:

- 5 VDC
- 9-28 VDC
- Power-Over-Ethernet (802.3af)

Model #	Relay Outputs	Contact Rating	Opto-Inputs	Input Range	Power Supply
Standard X-WR-1R12-115-5	1(SPDT)	12Amp @125V max	1	3-12 VDC	5VDC
Industrial X-WR-1R12-115-I	1(SPDT)	12Amp @125V max	1	3-12 VDC	9-28VDC
Industrial 11-28vdc X-WR-1R12-1124-I	1(SPDT)	12Amp @125V max	1	11-28 VDC	9-28VDC
POE X-WR-1R12-115-E	1(SPDT)	12Amp @125V max	1	3-12 VDC	POE / 5VDC

Available From:

CCTV Hire Pty Ltd
 Sydtech Express I.T. Solutions
 Phone: 02 9618 0444
 Fax: 02 9618 7583
 Email: info@cctvhire.com.au
 www.cctvhire.com.au